



Solutions

From Top to Bottom



HiServer-420A

4U Blade server chassis
Up to 10 server blades,
Powered by Intel® Xeon processor,
4GB memory, onboard storage,
Standard PCI-X expansion slot
Two networking blades and
management blades
2x12 ports Gigabit Ethernet Switch
Hot swappable 6+1 redundant modules,
Integrated smart KVM switch
Remote server control, deployment and
monitoring

סמן 13

Network Security Appliance

1-2U Rackmount network platform
Support Dual Intel® Xeon,
Pentium® 4-M, Pentium® III (Tualatin),
VIA C3 low power CPU
Built-in 3 to 12 Gigabit and 10/100
Ethernet ports
Internal HDD & CF option
PCI Expansions Options.

סמן 16



PEAK-7220VL2G

Dual Intel® Xeon / LV Xeon processors with
400/533MHz FSB up to 2.8GHz +
Intel® E7501 chipsets
Max. 8GB DDR (ECC) support
Dual Intel® 82545EM Gigabit Ethernet
controllers

סמן 14

PEAK-735

Intel® Pentium® 4 processor up to 3.2GHz +
800MHz FSB
Intel® 865G/ ICH5 chipsets
Serial ATA port (150MB/s) x2
USB 2.0 port (480Mbps) x2

סמן 17



EBC-572

Intel® Pentium® -M/ ULV/ LV Processor
High Speed AGP 4X for VGA display
Dual 10/100 Base-T Fast Ethernet
USB 2.0 Port x 4, Digital I/O, PC 104,
Compact Flash socket

סמן 15

EBC-365

Low power VIA Eden 667MHz
up to C3 1GHz processor
2D/3D graphic, TMDS(DVI optional)
TTL LCD(24-bit) interface
10/100Base-T fast Ethernet LAN
AC 97 ver.2.0 Audio, TV-out

סמן 18



PI/PV © 9586

